# **S Permatex**

# SAFETY DATA SHEET

Revision Date 18-May-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name 765-1216 NAPA SPRAY ADHESIVE (PTX82019) 11OZ

Other means of identification

Product Code 21143 Synonyms None

Recommended use of the chemical and restrictions on use
Recommended Use Aerosol Adhesive
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Distributor

ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

# Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1

### Label elements

Emergency Overview			
Danger			

Causes skin irritation

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol



Appearance White

Physical state Liquid Aerosol

Odor Solvent

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

### **Precautionary Statements - Storage**

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

- Toxic to aquatic life with long lasting effects
- The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (EINECS No. 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3

Unknown acute toxicity

12 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

# substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
PETROLEUM GASES, LIQUEFIED, SWEETENED	68476-86-8	30 - 60	*
N-HEXANE	110-54-3	10 - 30	*
ACETONE	67-64-1	10 - 30	*
CYCLOHEXANE	110-82-7	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

# **Description of first aid measures**

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash with soap and water. If symptoms persist, call a physician.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Call a physician or poison control center immediately. Do NOT induce

vomiting.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

### Unsuitable extinguishing media

None.

### Specific hazards arising from the chemical

Extremely flammable. Vapors may travel to source of ignition and flash back.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

contact with skin, eyes or clothing. Remove all sources of ignition. Take precautionary measures against static discharges. Contents under pressure. Do not puncture or

incinerate cans.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not puncture or

incinerate cans.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Keep away from sunlight, ignition sources and other sources of heat.

Incompatible materials Strong oxidizing agents, Acids

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m <sup>3</sup>	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m <sup>3</sup>
		(vacated) TWA: 180 mg/m <sup>3</sup>	
ACETONE	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
		(vacated) STEL: 2400 mg/m <sup>3</sup> The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	
CYCLOHEXANE	TWA: 100 ppm	TWA: 300 ppm	IDLH: 1300 ppm
110-82-7		TWA: 1050 mg/m <sup>3</sup>	TWA: 300 ppm
		(vacated) TWA: 300 ppm	TWA: 1050 mg/m <sup>3</sup>
		(vacated) TWA: 1050 mg/m <sup>3</sup>	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid; Aerosol

Appearance White Odor Solvent

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Flash point < -18 °C / < 0 °F Gives a flame projection at full valve opening or

Butyl acetate = 1

Air = 1

flashback at any degree of valve opening

Evaporation rate > 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:

Lower flammability limit:

No information available

No information available

Vapor pressure
No information available
Vapor density
>1

Relative density 0.73
Water solubility Negligible

Solubility in other solvents No information available Partition coefficient No information available No information available **Autoignition temperature Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available No information available **Explosive properties Oxidizing properties** No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 65%

**Density** No information available **Bulk density** No information available

# 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### **Chemical stability**

Stable under recommended storage conditions.

# **Possibility of Hazardous Reactions**

None under normal processing.

### Conditions to avoid

Heat, flames and sparks.

### **Incompatible materials**

Strong oxidizing agents, Acids

# **Hazardous Decomposition Products**

Carbon oxides

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation Harmful by inhalation. May cause drowsiness or dizziness.

**Eve contact** Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and

pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
N-HEXANE 110-54-3	= 25 g/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 48000 ppm (Rat) 4 h
ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m³ (Rat) 8 h
CYCLOHEXANE 110-82-7	> 5000 mg/kg (Rat)	> 2000 mg/kg ( Rabbit )	= 13.9 mg/L (Rat) 4 h

### Information on toxicological effects

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. Germ cell mutagenicity No information available. Carcinogenicity No information available.

**Target Organ Effects** Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system,

Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 18153 mg/kg ATEmix (dermal) 10777 mg/kg 440.9 mg/l ATEmix (inhalation-dust/mist) ATEmix (inhalation-vapor) 211200 mg/l

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

57 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
N-HEXANE 110-54-3	-	2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	1000: 24 h Daphnia magna mg/L EC50
ACETONE 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
CYCLOHEXANE 110-82-7	500: 72 h Desmodesmus subspicatus mg/L EC50	3.96 - 5.18: 96 h Pimephales promelas mg/L LC50 flow-through 23.03 - 42.07: 96 h Pimephales promelas mg/L LC50 static 24.99 - 44.69: 96 h Lepomis macrochirus mg/L LC50 static 48.87 - 68.76: 96 h Poecilia reticulata mg/L LC50 static	400: 24 h Daphnia magna mg/L EC50

# Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

# **Mobility**

No information available.

Chemical Name	Partition coefficient
PETROLEUM GASES, LIQUEFIED, SWEETENED	<=2.8
68476-86-8	
ACETONE	-0.24
67-64-1	
CYCLOHEXANE	3.44
110-82-7	

### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

# Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

**Contaminated packaging** Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE	-	Included in waste stream:	-	U002
67-64-1		F039		
CYCLOHEXANE	-	-	-	U056
110-82-7				

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
N-HEXANE	Toxic
110-54-3	Ignitable
ACETONE 67-64-1	Ignitable

# 21143 - 765-1216 NAPA SPRAY ADHESIVE (PTX82019) 110Z

CYCLOHEXANE	Toxic
110-82-7	Ignitable

### 14. TRANSPORT INFORMATION

DOT

**UN/ID no** 1950

**Proper shipping name:** Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 Emergency Response Guide 126

Number

<u>IATA</u>

**UN/ID no** ID 8000

**Proper shipping name:** Consumer commodity

Hazard Class 9 ERG Code 9L

**IMDG** 

**UN/ID no** 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1 EmS-No F-D, S-U

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies Complies **DSL/NDSL** Complies **EINECS/ELINCS** Not Listed. **ENCS** Complies **IECSC KECL** Complies Complies **PICCS AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0
CYCLOHEXANE - 110-82-7	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No

### **Reactive Hazard**

No

# **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
CYCLOHEXANE 110-82-7	1000 lb	-	-	Х

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
N-HEXANE	5000 lb	-	RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ
ACETONE	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
CYCLOHEXANE	1000 lb	-	RQ 1000 lb final RQ
110-82-7			RQ 454 kg final RQ

# **US State Regulations**

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
N-HEXANE 110-54-3	Х	X	Х
CYCLOHEXANE 110-82-7	X	X	Х

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA Health hazards 2 Flammability 3 Instability 0 -

Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 18-May-2015

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**